0
365
4
- 10
Seed
254%
14
0
g sile
j.
ipali:
111
0
1

Please type a plue sign (+) inside this box -> +		PTO/BEAGS (27) Approved for use through 96/30/2000. Olds 9661-00 Patent and Trademark Office: U.S. DEPARTMENT OF COMMEN		
*		nd to a collection of information unless it displays a valid QMB control rughts by Docket No. May 4861 / UV 1.46		
F UTILITY		- 170-40017HK-140		
F PATENT APPLICATION	-			
TRANSMITTAL	Title	DEVICE FOR INSERTING AND REMOVING		
Only for new nonprovisional applications under 37 C F R § 1 53(b))) Expres	as Mail Label No. EE415238795US		
APPLICATION ELEMENTS		Appress TO: Box Patent Application		
See MPEP chapter 600 concerning utility patent application conte	nts	Weshington, DC 20231		
1. X * Fee Transmittal Form (e.g., PTO/SB/17)		6. Microfiche Computer Program (Appendix)		
(Submit an original and a duplicate for fee processing) Y Specification Total Pages O	٦,	7. Nucleotide and/or Amino Acid Sequence Submission		
(preferred errangement set forth below)	٦,	(if applicable, all necessary) a. Computer Readable Copy		
- Descriptive title of the Invention				
- Cross References to Related Applications - Statement Regarding Fed sponsored R & D		b. Paper Copy (Identical to computer copy)		
- Reference to Microfiche Appendix		c. Statement verifying identity of above copies		
- Background of the Invention		ACCOMPANYING APPLICATION PARTS		
- Brief Summary of the Invention		8. X Assignment Papers (cover sheet & document(s))		
- Brief Description of the Drawings (if filed)		9 37 C.F.R.§3.73(b) Statement Power of Attorne		
- Detailed Description		(when there is an assignee) Power of Attorne		
- Claim(s) - Abstract of the Disclosure		10. English Translation Document (If applicable)		
3. X Drawing(s) (35 U.S.C. 113) [Total Sheets 4	7,	11. Information Disclosure Copies of IDS Statement (IDS)PTO-1449 Citations		
5. A Daniel (1) (1) (1) (1)	≓′	1 =		
4. Oath or Declaration [Total Pages 2	1	LJ		
a. X Newly executed (original or copy)		13. X Return Receipt Postcard (MPEP 503) (Should be specifically itemized)		
b. Copy from a prior application (37 C.F.F.	£ § 1.63(d	Small Entity Statement filed in prior applicati		
[Note Box 9 below]		14. Statement(a) Status still proper and desired		
DELETION OF INVENTOR(S) Signed statement attached de	leting	15. X Certified Copy of Priority Document(s)		
inventor(s) named in the prior as see 37 C.F.R. §§ 1.63(d)(2) and	plication,	16. Other:		
5 Incorporation By Reference (useeble # Box 40 to ca	hecked)			
The entire disclosure of the prior application, fro copy of the oath or declaration is supplied under	m which s r Boy 4h	IS PACE TO PAY SMALL BOTTY STATEMENT IN ROUNCED OF CFAL \$ 1.17, DICE.		
considered to be part of the disclosure of the ac	companyi	""V BJF OME PEED BLA PRICE APPLICATION & RELIED UPON G7 C.F.R. \$ 1.30.		
application and is hereby incorporated by refere	nce there	in. upply the requisite information below and in a proliminary amendment:		
	on-in-part (
Prior application information: Examiner		Group / Art Unit:		
	SPONDE	ENCE ADDRESS		
:	********			
Customer Number or Ber Code Label	- 41 411	or 🖾 Correspondence address below		
; (Insert Custome	NO. OF ALE	ach ber code label hera)		
Name Bayer Corporation				
Address Patent Department				
100 Bayer Road		r		
Cay Pittsburgh	State	PA Zp Code 15205-9741		
Country U.S.A. Tele	phone	(412) 777-2349 F (412) 777-5449		

Signature

Signature

Date

11-18-98

Burden Hour Statement: This form is self-mised to base 0.2 foort is complete. They will very depending upon to needs of first individual case committee on the amount of first you are received to complete this form should be larget to the Chief Information Officer, Palent and Tradament Healthrighton, Co. 2023 1.0 DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Palentia, Box Palenti Application, Weshington, DC 20231.

39,138

Noland W

Approved for use Prough IsoS/2000. Oxide Palent and Tablemant Officer U.S. DEFARTEBENT OF C: Under the Papenwork Reduction Act of 1996, no persons are required to respond to a collection of information unless it displays a valid CMB conta						
	Complete If Known					
EEE TOANGMITTAL	Application Number To Be Assigned					

Application Number	To Be Assigned		
Filing Date	Herewith		
First Named Inventor	Bernd Willing		
Examiner Name			
Group / Art Unit			
Attorney Docket No.	Mo-4861/HE-146		
	Filing Date First Named Inventor Examiner Name Group / Art Unit		

101AE AMOUNT OF TATMETT (0) 000:00	Aziomey Docket No. Mo-4861/HE-146	
METHOD OF PAYMENT (check one)	FEE CALCULATION (continued)	
The Commissioner is hereby surhorized to charge indicated fees and credit any over payments to: Decosit: Decosit:	3. ADDITIONAL FEES Large Entity Small Entity Fee Fee Fee Fee Fee Fee Fee Description Code (5) Code (5)	Fee Paid
Account 13-3848	105 130 205 65 Surcharge - late filing fee or ceth	
Deposit Account Bayer Corporation	127 50 227 26 Surcharge - late provisional filing fee or cover sheet.	
Charge Any Additional Charge the Issue Fee Set in	139 130 139 130 Non-English specification	1 1
Fee Required Under 37 C.F.R. § 1 18 at the Melling 37 C.F.R. §§ 1,16 and 1,17 of the Notice of Allowance	147 2,520 147 2,520 For filing a request for resommination	
or Grand and Control of Control	112 920° 112 920° Requesting publication of SIR prior to	
2. Payment Enclosed: Check Money Other	113 1,840° 113 1,840° Requesting publication of SIR after Examiner action	
	115 110 215 55 Extension for reply within first month	
FEE CALCULATION	118 400 218 200 Extension for reply within second month	
1. BASIC FILING FEE	117 950 217 475 Extension for reply within third month	
Large Entity Small Entity	118 1,510 218 755 Extension for reply within fourth month	
Fee Fee Fee Fee Fee Description Fee Paid Code (\$) Code (\$)	128 2,060 228 1,030 Extension for reply within fifth month	
101 790 201 395 Utility filing fee 760.00	119 310 219 155 Notice of Appeal	
106 330 206 185 Design filling fee	120 310 220 155 Filling a brief in support of an appeal	
107 540 207 270 Plant filing fee	121 270 221 135 Request for oral hearing	
108 790 208 395 Reisaus filing fee	138 1,510 138 1,510 Petition to inetitute a public use proceeding	
114 150 214 75 Provisional fling fee	140 110 240 55 Petition to revive - unavoidable	—
SUBTOTAL (1) (\$) 760.00	141 1,320 241 860 Petition to revive - unintentional	
2. EXTRA CLAIM FEES	142 1,320 242 860 Utility leave fee (or releave)	
Extra Claims below Fee Paid	143 450 243 225 Deelgn issue fee	
Total Claims 6 -20** - X =	144 670 244 335 Plant leave fee	
Independent . 3** = X	122 130 122 130 Pelitions to the Commissioner	
Multiple Dependent =	123 50 123 50 Petitions related to provisional applications	
**or number previously paid, if greater; For Reissues, see below Large Entity Small Entity	126 240 126 240 Submission of information Disclosure Stmt.	
Fee Fee Fee Fee Fee Description Code (\$) Code (\$)	581 40 581 40 Recording each patent assignment per property (times number of properties)	40.00
103 22 203 11 Claims in excess of 20	146 790 246 395 Filing a submission after final rejection (37 CFR 1.128(a))	
102 82 202 41 Independent claims in excess of 3	149 790 249 395 For each additional invention to be	\vdash
104 270 204 135 Multiple dependent claim, if not paid	examined (37 CFR 1.129(b))	
109 82 209 41 "Reissue independent claims over original petent 110 22 210 11 "Reissue claims in excess of 20	Other fee (specify)	
and over original petent	Other fee (specify)	
SUBTOTAL (2) (\$)	* Reduced by Basic Filing Fee Paid SUBTOTAL (3) (\$)	40.00
SUBMITTED BY	Complete (if applic	(elde:

SUBMITTED B	Υ					Complete (#	applicable)
Typed or Printed Name	Noland	J Chewn	2			Reg. Number	39,138
Signature		12		Dete	11-18-98	Deposit Account User ID	

Burden Hour Statement This form is estimated to take 0.2 holds to complete. Time will very depending upon the needs of the inclinitual case. Any comments on the amount of time you ser required to complete the firem should be sent to the Chief Information Officer, Patient and Tradement Officer, Westington, CC 20231. Do NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissionar for Patients, Westington, CC 20231.

Mo-4861 HF-146-US/FC

5

10

15

20

25

30

DEVICE FOR INSERTING AND REMOVING WORK STATIONS CIRCULATING ON A CHAIN

BACKGROUND OF THE INVENTION

To carry out a uniform sequence of working steps at a plurality of work stations, frequently, each individual working step is repeated at a stationary position, wherein a plurality of work stations, driven on a belt or a chain, passes by the location in which each particular working step is carried out.

A uniform sequence of working steps may, for example, be the assembly of a device, wherein the various assembly steps are carried out at different locations and the part to be assembled is moved on a work station from location to location for the various assembly steps to be carried out. A similar arrangement may be used in the production of molded parts, in which the working steps comprise cleaning the mold, providing the mold with a release agent, inserting a displacement body, filling the mold for the first time, curing the first molded part, removing the displacement body, filling the mold for the second time, curing the second mold contents, opening the mold and removing the molded part. Such working steps are carried out at different locations, wherein the mold is conveyed on a work station from one location to the other.

The work stations may take the form of work station wagons, wherein the work station wagons are moved by means of connection elements to the circulating chain drive which are provided and/or engaged on the wagons on one side.

The design of work stations in the form of independent work station wagons is particularly applicable when the initial and/or subsequent fitting out of the work station, or intermediate working steps which cannot be carried out on the chain, are carried out away from the conveyor system in

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Donna J. Veatch

(Name of person mailing paper or fee)
Signature of person mailing paper or fee)

15

20

Mo-4861 - 2 -

terms of location. In this case, it may be necessary to remove individual work station wagons from the chain cycle and/or insert them into it.

SUMMARY OF THE INVENTION

The present invention relates to a device for carrying out a sequence of working steps on travelling work station wagons comprising

- a) an oval track wherein said work station wagons are circulating, wherein said wagons comprise at least one detachable connection element connected to a circulating chain which moves said wagons;
- b) at least one insertion and at least one removal guide track is provided on the outside of said oval track, wherein said at least one insertion and at least one removal guide track comprises a transfer point to which the chain is allocated:
- c) at least one coupling element is further provided at each transfer point via which the wagons may be coupled into the guide tracks on the side opposite of the side of said wagons comprising at least one detachable element, with at least one switchable points element located on said guide track, which during the insertion position, release said at least one coupling element and bring about the engagement of said detachable connection element to said chain or during the removal position, couple the coupling elements and removably detach said at least one detachable connection from said chain.

BRIEF DESCRIPTION OF THE DRAWINGS

- Fig. 1 is a diagram of the device of the present invention.
- 25 Fig. 2 is an enlarged diagram of the device of the present invention showing the circulating chain drive with a guide channel.
 - Fig. 3 shows an enlarged view of the points tongues of the device of the present invention.
- Fig. 4 shows an enlarged view of the insertion of wagon X into the 30 device of the present invention.

10

15

20

25

30

DETAILED DESCRIPTION OF THE INVENTION

The present invention provides a device for carrying out a uniform sequence of working steps on travelling work station wagons circulating on an oval track, wherein the wagons are moved by means of detachable connection elements to a circulating chain drive. The detachable connection elements are provided and/or engaged on one side of the wagon. The device of the present invention also composes at least one insertion and at least one removal guide track, to each of which a transfer point to the chain is allocated and is provided on the outside of this oval conveyor system. Coupling elements are further provided via which the wagons may be coupled into the guide tracks. On the other side of the wagon, switchable points elements are provided, in which insertion/removal positions release the connection elements and couple the coupling elements for removal purposes and/or uncouple the coupling elements and bring about the engagement of the connection elements for insertion purposes, which are provided at each transfer point.

An embodiment of the present invention comprises the chain circulating in an oval, for example, and the chain running in a guide channel. The wagons have guide rollers running on vertically projecting mountings in the guide channel and the wagons also comprise at least one carrier pin, wherein carrier cages located on the chain removably engage the carrier pin on the wagon. On the chain side, the transfer point may be designed in such a way that the outer boundary of the guide channel is interrupted so that the guide rollers may emerge laterally out of the guide channel and the carrier pin laterally out of the carrier cage which is open towards the outside.

In an embodiment of the present invention, the insertion and removal tracks may take the form of guide channels which are arranged parallel to the chain drive and at a distance from its guide channel, wherein the distance between the chain and the guide channel of the

10

15

20

25

30

Mo-4861 - 4 -

insertion/removal track approximately corresponds to the width of the work station wagon. On the outside of the wagon, guide rollers are then also provided, which run in the guide channel of the removal guide track after transfer from the chain to the removal guide track. At the transfer point, the guide channel of the removal guide track has interruptions, which are closed by means of points tongues if no transfer is to take place. If the wagon, which passed by the transfer point is to be removed, the points tongues are switched in such a way that they guide the guide rollers of the wagon into the guide channel of the removal track.

The insertion point is correspondingly designed. When inserting a wagon, care should be taken to ensure that the work station wagon is inserted in an accurately positioned manner with respect to the connection element to the chain, and with respect to the embodiment of the present invention, that the carrier pin of the wagon is introduced into the carrier cage of the chain.

Therefore, the present invention preferably provides that each work station wagon has a spacer with respect to the next wagon, wherein the spacing of the connection element parts on the chain (i.e., the carrier cages) have a spacing which corresponds to the length of the wagon and spacer combined. In this way, the wagon to be inserted is inserted at the free place on the chain, wherein the following wagon with its spacer pushes the wagon to be inserted precisely into the position in which the connection to the chain takes place.

Preferably, the insertion guide track has a load-dependent drive in which the maximum speed is higher than the chain speed. Preferably, the insertion guide track has a friction drive, which engages on the outer side (relative to the oval) of the wagon. This ensures that prior to transfer, the wagon to be inserted has a higher speed than the following wagon on the chain, so that during the transfer, the wagon to be inserted is pushed into the transfer position by the spacer of the following wagon.

10

15

20

25

30

Mo-4861 - 5 -

The invention will be explained in greater detail with the aid of the drawings which follow:

Fig. 1 shows a carousel 10, with the chain 1, circulating in an oval, on which the work station wagons denoted by Roman numerals circulate. A removal guide track 20 and an insertion guide track 30 are also shown in diagrammatic form. The transfer points are denoted by the broken-lined circles 21 and 31.

The enlarged view of Fig. 2 shows that the circulating chain drive 1 comprising a guide channel 2, which is formed by the two guide strips 5 and 6, wherein the drive chain 3 runs inside the guide channel 2. The chain has carrier cages 4a, 4b, functioning as a connection element part on the chain side to receiving such connection element from the wagon. The carrier cages 4a, 4b are arranged at a regular spacing. Guide rollers 7a, 7b, which run in the channel 2 as long as the wagon is guided on the chain are provided laterally on the work station wagons denoted by Roman numerals and are removably fastened to carrier cages 4a and 4b, respectively.

The removal guide track 20 also consists of a channel 22, which is formed by guide strips 25 and 26. On the side facing away from the chain drive the work station wagons have guide rollers 8a and 8b which in the event of transfer are engaged by switchable points tongues 27a and 27b and are guided into the guide channel 22 of the removal guide track 20; see wagon II. On the side opposite the points 27a and 27b, the guide strip 5 comprises a break or interruption so that the guide rollers 7a and 7b belonging to the wagon to be removed, are moved out of the guide channel 2 and out of the carrier cage 4a and 4b, respectively.

Fig. 3 shows an enlarged view of the points tongues, wherein the numerals denote elements identical with Fig. 2. The top view shows the points tongues in the "transit" position, the bottom view shows the points tongues in the "transfer" position.

10

15

20

25

Mo-4861 - 6 -

Fig. 4 shows the insertion of wagon X, still in the waiting position in Fig. 2, at the position in which wagon II is removed in Fig. 2. The end phase of the insertion, which explains the correct position for connection to the chain 3, is shown. In the region of the deflection 40 of the chain, the work station wagons are considerably wider apart. In this region, wagon X is initially pushed in front of wagon I. At the time of transfer, i.e., when the guide rollers 8a and 8b of wagon X reach the points tongues 37a and 37b, wagon X to be inserted, is accurately positioned between wagons I and III via the spacer 9 so that the guide rollers 7a and 7b are accurately positioned in the carrier cages 4a and 4b of the chain 3.

It will be readily apparent to the person skilled in the art that the connection elements between circulating chain and work station wagons, and the coupling elements to the insertion and removal guide tracks, may be designed differently from the views shown by way of example. For example, they may take the form of switchable electromagnets or rocker heels. It is essential to the invention that the guiding of the work station wagons for the purposes of this invention, insertion takes place on the one side and removal takes place on the other side, so that complicated points, in which that wagons must pass over structures, are avoided on the circulating chain drive. Both the circulating chain drive and the insertion and removal guide tracks may be arranged above the shopfloor without forming obstacles to the work station wagons travelling on their own wheels.

Although the invention has been described in detail in the foregoing for the purpose of illustration, it is to be understood that such detail is solely for that purpose and that variations can be made therein by those skilled in the art without departing from the spirit and scope of the invention except as it may be limited by the claims.

15

20

25

WHAT IS CLAIMED IS:

- A device for carrying out a sequence of working steps on travelling work station wagons comprising
- a) an oval track wherein said work station wagons are circulating, wherein said wagons comprise at least one detachable connection element connected to a circulating chain which moves said wagons;
- at least one insertion and at least one removal guide track is provided on the outside of said oval track, wherein said at least one
 insertion and at least one removal guide track comprises a transfer point to which the chain is allocated:
 - c) at least one coupling element is further provided at each transfer point via which the wagons may be coupled into the guide tracks on the side opposite of the side of said wagons comprising at least one detachable element, with at least one switchable points element located on said guide track, which during the insertion position, release said at least one coupling element and bring about the engagement of said detachable connection element to said chain or during the removal position, couple the coupling elements and removably detach said at least one detachable connection from said chain.
 - 2. A device according to Claim 1, wherein each work station wagon has a spacer which defines the minimum distance between two wagons on said chain and the distance between said chain wherein said detachable connection element is removably connected to the chain at the transfer point is dimensioned in such a way that the wagons allocated to said detachable connection elements have touch-contact via the spacer.
 - A device according to Claim 1, wherein during insertion or removal of said wagon to said device, during transfer, said wagon to be transferred is pushed into position by the following wagon.


- 8 -


- A device according to Claim 1, wherein said insertion guide track has a load-dependent drive, the maximum speed of which is higher than the chain speed.
- A device according to Claim 4, wherein said drive is a friction
 drive.
 - A device according to Claim 1, wherein said chain comprises at least one carrier cage to receive said at least one detachable connection element.


DEVICE FOR INSERTING AND REMOVING WORK STATIONS CIRCULATING ON A CHAIN

ABSTRACT OF THE DISCLOSURE


A device for carrying out a sequence of working steps on travelling work station wagons comprising an oval track wherein said work station wagons are circulating, wherein said wagons comprise at least one detachable connection element connected to a circulating chain which moves said wagons; at least one insertion and at least one removal guide track is provided on the outside of said oval track, wherein said at least one insertion and at least one removal guide track comprises a transfer point to which the chain is allocated; at least one coupling element is further provided at each transfer point via which the wagons may be coupled into the guide tracks on the side opposite of the side of said wagons comprising at least one detachable element, with at least one switchable points element located on said quide track, which during the insertion position, release said at least one coupling element and bring about the engagement of said detachable connection element to said chain or during the removal position, couple the coupling elements and removably detach said at least one detachable connection from said chain.







COUNTY! MODINGTOD



As a below named inventor, I hereby declare that:

the specification of which is attached hereto,

or was filed on

My residence, post office address and citizenship are as stated below next to my name. I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

DEVICE FOR INSERTING AND REMOVING WORK STATIONS CIRCULATING ON A CHAIN

Application Serial No.			_		
I hereby state that identified specification			erstand the o	contents	of the above-
I acknowledge the dability of this applications, \$1.56(a).	uty to disclose ation in accore	e informatio dance with	on which is n Title 37, Co	naterial i de of Fe	to the patent- ederal Regula-
I hereby claim foreign of any foreign appl and have also identi- certificate having a is claimed:	ication(s) for fied below any	patent or foreign a	inventor's c opplication for	ertificate patent	listed below or inventor's
Prior Foreign Applica	tion(s), the pr	riority(ies)	of which is/a	re to be	claimed:
19752750.7 (Number)	Germany (Country)		November 28, (Month/Day/		d)
I hereby claim the benefit under Title 35, United States Code, \$120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, \$112, I acknowledge the duty to disclose the material information as defined in Title 37, Code of Federal Regulations, \$1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:					
(Application Serial N	lo.)	(Filing Dat	e)	(patented,	(Status) pending, abandoned)
(Application Serial N	No.)	(Filing Dat	ce)	(patented,	(Status) pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent

issued thereon.

POWER OF ATTORNEY: As a named invenior, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

JOSEPH C. GIL, Patent Office Registration Number 26,602
ARON PREIS, Patent Office Registration Number 29,426
LYNDANNE M. WHALEN, Patent Office Registration Number 29,457
THOMAS W. ROY, Patent Office Registration Number 29,852
RICHARD E. L. HENDERSON, Patent Office Registration Number 31,619
GODFRIED R. AKORLI, Patent Office Registration Number 28,779
N. DENISE BROWN, Patent Office Registration Number 36,097
NOLAND J. CHEUNG, Patent Office Registration Number 39,761
DIDERICO VAN EYL, Patent Office Registration Number 39,641

all of Bayer Corporation, Pittsburgh, Pennsylvania 15205-9741

Send Correspondence To:	Direct Telephone Calls To:
Patent Department	
Bayer Corporation	(412) 777-2349
100 Bayer Road	
Pittsburgh, Pennsylvania 15205-9741	

FULL NAME OF SOLE OR FIRST INVENTOR Bernd WILLING	INVENTOR'S SIGNATURE D	ATE 16198
RESIDENCE	CITIZENSAIP	
53225 Bonn.	German	
POST OFFICE ADDRESS		
Stiftsstr. 8. 53225 Bonn.		